



Performance Data 50Hz

MODEL (50Hz)		P2		Delivery											
1 - 220-240V	3 - 380 - 415V	kW	HP	n≈2850 1/min											
				m³/h	0	1.8	3.6	5.4	7.2	9.0	10.8	12.6	14.4	16.2	
				l/min	0	30	60	90	120	150	180	210	240	270	
4SDM12/4	4SD12/4	0.75	1	HEAD (m)	27	26	25	23	21	19	17	15	12	7	
4SDM12/5	4SD12/5	1.1	1.5		34	33	31	28	27	24	22	19	15	9	
4SDM12/6	4SD12/6	1.1	1.5		41	39	37	34	32	29	26	23	18	11	
4SDM12/7	4SD12/7	1.5	2		47	46	43	39	37	34	31	26	21	12	
4SDM12/8	4SD12/8	1.5	2		54	52	49	45	43	39	35	30	24	14	
SDM12/10	4SD12/10	2.2	3		68	65	61	56	53	49	44	38	30	18	
4SDM12/12	4SD12/12	2.2	3		81	78	74	68	64	58	52	45	36	21	
4SDM12/14	4SD12/14	3	4		95	91	86	79	75	68	61	53	42	25	
4SDM12/16	4SD12/16	3	4		108	104	98	90	85	78	70	60	48	28	
	4SD12/18	4	5.5		122	117	110	101	96	88	79	68	54	32	
	4SD12/21	4	5.5		142	137	129	118	112	102	92	79	63	37	
	4SD12/25	5.5	7.5		169	163	153	143	133	122	109	94	75	44	
	4SD12/30	7.5	10		203	195	184	169	160	146	131	113	90	53	